

# T25

U SERIES

The T25 is the ideal general-purpose loudspeaker with a wide frequency response, suitable for all kinds of mid-field theatre and live venue applications that require professional sound quality.

## FEATURES

- Very high SPL from a full range passive enclosure
- Extended low frequency performance from dual 15" drivers
- Dedicated low distortion bass-mid driver
- User rotatable 90° x 50° horn
- 2" (50mm) exit titanium dome compression driver
- Multi-laminate plywood construction



## Specifications

<b>FREQUENCY RESPONSE(-3dB)</b>	40 Hz-18kHz	
<b>DRIVERS</b>	2 x 15 " (385mm)/4 " (100mm)voice coil Woofer 1 x 2 " (50mm) exit compression driver	
<b>RATED POWER</b>	1100W RMS,4000W peak	
<b>SENSITIVITY</b>	101dB 1watt/1 metre	
<b>MAXIMUM SPL</b>	131dB continuous,137 dB peak	
<b>PASSIVE</b>	1± Speaker	3± NC
	2± NC	4± NC
<b>BI-AMP</b>	1± LF	3± HF
	2± MF	4± NC
	LF: 1000W 4Ω	
	HF : 100 W 8Ω	
<b>DISPERSION(-6dB)</b>	90 ° x 50 °	
<b>CROSSOVER FREQUENCIES</b>	1.5 kHz passive	
<b>INPUT CONNECTORS</b>	2 x Speakon NL4	
<b>PACKAGE SIZE</b>	617mm x 596mm x 1345mm	
<b>NET WEIGHT</b>	70kg	
<b>GROSS WEIGHT</b>	78kg	

## Configuration

