

U215

U SERIES

The U215 is the ideal general-purpose loudspeaker with a wide frequency response, suitable for all kinds of mid-field theatre and live venue applications that require professional sound quality.

FEATURES

- Very high SPL from a full range passive enclosure
- Extended low frequency performance from dual 15" drivers
- Dedicated low distortion bass-mid driver
- User rotatable 90° x 50° horn
- 2" (50mm) exit titanium dome compression driver
- Multi-laminate plywood construction



Specifications

FREQUENCY RESPONSE(-3dB)	40 Hz-18kHz	
DRIVERS	2 x 15 " (385mm)/4 " (100mm)voice coil Woofer 1 x 2 " (50mm) exit compression driver	
RATED POWER	1100W RMS,4000W peak	
SENSITIVITY	101dB 1watt/1 metre	
MAXIMUM SPL	131dB continuous,137 dB peak	
PASSIVE	1± Speaker	3± NC
	2± NC	4± NC
BI-AMP	1± LF	3± HF
	2± MF	4± NC
	LF: 1000W 4Ω	
	HF : 100 W 8Ω	
DISPERSION(-6dB)	90 ° x 50 °	
CROSSOVER FREQUENCIES	1.5 kHz passive	
INPUT CONNECTORS	2 x Speakon NL4	
PACKAGE SIZE	617mm x 596mm x 1345mm	
NET WEIGHT	70kg	
GROSS WEIGHT	78kg	

Configuration

